

Tri-Proof LED Fixture

The IL-Tek Tri-Proof light is designed for liquid tight, optimal illumination of agricultural, commercial and industrial locations. The entire fixture is designed to meet and exceed **4X** performance standards in a wide variety of lighting applications.




FEATURES

- **110 lm/watt (Super Bright LED's)**
- **Water proof, Dust Proof, Corrosion proof**
- **Innovative, stylish easy clean surface**
- **Light weight, liquid tight modular construction**
- **Super-fast installation, suspended or surface mounted**
- **Reliable low voltage series drivers for safe operation**
- **Built in 1-10V dimming function**

APPLICATIONS

- Agriculture
- Commercial/Industrial
- Tunnels
- Corridors
- Warehousing

SPECIFICATIONS

Dimensions	40W, 13x2.4" (1150 x 76 x 60mm)
Power & Lumen Output	4400 lm @ 5000K
Dimming Function	1-10V
Color Temperature CCT	5000K (Day White)
Color Rendering Index	>80
Rated Life (L80)	5 Years (DOP) / 50,000 Hours
Housing	High Impact 1 PC Extrusion (Poly Carbonate)
Beam Spread	110°
Operating Temperature	-4°F to +104°F (-20°C to +40°C) Amb
Input Voltage	100 -277V/AC
Power Factor	>0.95
Working Voltage & Current	
40 W	33±2V/DC & 1050mA
Net Weight	3.25lb (1.47kg)
Installation	Bracket Mounted Ceiling/Wall
NA Approvals	 /4X

