

# IL-Tek 15-Watt LED Fixture

The IL-Tek 15-watt high efficiency luminaire is designed for liquid tight, optimal illumination of agricultural, commercial and industrial locations. The luminaire is designed to provide reliable, consistent performance in a wide variety of lighting applications.

## FEATURES

- Suitable for wet/damp locations
- 160-degree beam spread (reduced-glare from frosted globe lens)
- Driver provides consistent output over varying voltage conditions
- Surge protection (0- 2500 volts)
- Lightweight, impact resistant, anti-corrosive enclosure/lens
- Energy efficient – designed to replace 100W incandescent or 25 watt CFL
- Adaptor compatibility with most jelly jar junction boxes
- Easy installation with E26 socket connector
- Low maintenance
- Low operating temperature – Aluminum/plastic heatsink

## SPECIFICATIONS

<b>Power &amp; Lumen Output</b>	15 watt/1600lm (107lm per watt)
<b>Dimensions</b>	4.09 x 6.10 inches (104x155mm)
<b>Color Temperature CCT</b>	5000K (Day White)
<b>Color Rendering Index</b>	>80
<b>Rated Life (L80)</b>	5 Years (DOP) / 50,000 Hours
<b>Beam spread</b>	160° Degree
<b>Operating Temperature</b>	-20C to +45C (-4F to 113F)
<b>Input Voltage</b>	100–130VAC 60hz
<b>Dimmable</b>	TRIAC Dimmable (5-100%)
<b>Power factor</b>	>0.95
<b>Environmental</b>	Suitable for wet & damp locations (IP-66)



## INCLUDES

15W Fixture, Hardwire Connector

## ACCESSORIES

E26 Socket Connector, Junction Box Adaptor (1 pc), Silicone Adaptor Gasket (1 pc), Stainless Steel Mounting Screws (2 pcs)

## APPLICATIONS

- Agriculture
- Commercial/Industrial
- Tunnels
- Corridors
- Warehousing

